

Proper Orthogonal Decomposition for Optimal Control Problems with Mixed Control-State Constraints

Workshop on Numerical Methods
for Optimal Control and Inverse Problems

Technische Universität München

Martin Gubisch, Stefan Volkwein

University of Konstanz

March 11

Universität
Konstanz



Problem formulation

$$\min_{(y,u) \in Y \times U} J(y, u) = \frac{1}{2} \|y - y_Q\|_{L^2(0,T;H)}^2 + \frac{\kappa}{2} \|u\|_U^2 \quad (*)$$

subject to

$$\begin{aligned} \langle \dot{y}(t), \varphi \rangle_{V^*, V} + \langle \nabla y(t), \nabla \varphi \rangle_H &= \langle (\mathcal{B}u + f)(t), \varphi \rangle_{V^*, V} & (\varphi \in V = H_0^1(\Omega)) \\ \langle y(0), \varphi \rangle_H &= \langle y_0, \varphi \rangle_H & (\varphi \in H = L^2(\Omega)) \end{aligned}$$

and

$$\varepsilon u(t) + (\mathcal{I}y)(t) \leq u_b(t)$$

with $U = L^2(0, T; \mathbb{R}^m)$ and $\mathcal{B} : U \rightarrow L^2(0, T; H)$, $\mathcal{I} : L^2(0, T; H) \rightarrow U$ given by

$$(\mathcal{B}u)(t, x) = \sum_{i=1}^m u_i(t) \chi_i(x), \quad (\mathcal{I}y)(t) = \left(\int_{\text{supp}(\chi_i)} y(t, x) dx \right).$$



Existence and uniqueness

THEOREM. Assume that the closed, convex and bounded set

$$X_{\text{ad}} = \{(y, u) \in Y \times U \mid \dot{y} - \Delta y = \mathcal{B}u + f \text{ \& } y(0) = y_0 \text{ \& } \varepsilon u + \mathcal{I}y \leq u_b\}$$

is nonempty. Then there exists a unique solution (\bar{y}, \bar{u}) to (*).

Further, there is a unique pair of Lagrange multipliers $(\bar{p}, \bar{\lambda})$ such that

$$\begin{aligned}\dot{\bar{y}}(t) + \langle \nabla \bar{y}(t), \nabla \cdot \rangle_H - (\mathcal{B}\bar{u} + f)(t) &= 0 \\ y(0) - y_0 &= 0\end{aligned}$$

$$\begin{aligned}-\dot{\bar{p}}(t) + \langle \nabla \bar{p}(t), \nabla \cdot \rangle_H + (\mathcal{I}^* \bar{\lambda})(t) + (\bar{y} - y_Q)(t) &= 0 \\ \bar{p}(T) &= 0\end{aligned}\tag{**}$$

$$\kappa \bar{u}(t) - (\mathcal{B}^* p)(t) + \varepsilon \bar{\lambda}(t) = 0$$

$$\bar{\lambda}(t) - \chi_{\mathcal{A}_b(y, p)} \left(\frac{1}{\varepsilon} \mathcal{B}^* p + \frac{\kappa}{\varepsilon} \mathcal{I}y - \frac{\kappa}{\varepsilon^2} u_b \right) = 0$$



Primal-dual active set strategy

Algorithm (Primal-dual active set strategy)

Require: Initial state-adjoint state pair $(y^0, p^0) \in Y \times Y$.

- 1: Set $k = 0$
 - 2: **repeat**
 - 3: Calculate active set $\mathcal{A}_b(y^k, p^k)$
 - 4: Solve the primal-dual system $(**)$ to get (y^{k+1}, p^{k+1})
 - 5: Set $k = k + 1$
 - 6: **until** $\mathcal{A}_b(y^k, p^k) = \mathcal{A}_b(y^{k-1}, p^{k-1})$
 - 7: Return $\bar{u} = u(y^k, p^k)$.
-



Proper orthogonal decomposition (POD)

Problem: After elimination of u, λ , the discrete linear system $(**)$ is still of the dimension $2N_t N_x$.

Idea: For $\ell \ll N_x$, find an *optimal* finite element basis $(\psi_1, \dots, \psi_\ell)$ such that the corresponding Galerkin solution y^ℓ is close to \bar{y} .

THEOREM. Let $y_{\text{FE}} \in \mathcal{C}^1(0, T; \mathbb{R}^{N_x})$ an FE solution to the state equation. Consider the operators $\mathcal{Y} : L^2(0, T; \mathbb{R}) \rightarrow \mathbb{R}^{N_x}$ and $\mathcal{Y}^* : \mathbb{R}^{N_x} \rightarrow L^2(0, T; \mathbb{R})$,

$$\mathcal{Y}\phi = \langle \phi, y_{\text{FE}} \rangle_{L^2(0, T; \mathbb{R})} \in \mathbb{R}^{N_x}, \quad \mathcal{Y}^*\phi = \langle \phi, y_{\text{FE}}(\cdot) \rangle_H \in L^2(0, T; \mathbb{R}).$$

Let $\psi^\ell = (\psi_1, \dots, \psi_\ell)$ eigenvectors to $\mathcal{Y}\mathcal{Y}^* : \mathbb{R}^{N_x} \rightarrow \mathbb{R}^{N_x}$ corresponding to the ℓ largest eigenvalues. Then ψ^ℓ solves the minimization problem

$$\min_{\substack{i=1, \dots, \ell \\ \langle \phi_i, \phi_j \rangle_H = \delta_{ij}}} \left\| y_{\text{FE}} - \underbrace{\sum_{i=1}^{\ell} \langle y_{\text{FE}}, \phi_i \rangle_H \phi_i}_{=y^\ell} \right\|_H^2.$$

Universität
Konstanz



Reduced order modeling (ROM)

Algorithm (Reduced order modeling)

Require: $\ell \ll N_x$, initial control guess $u^\ell \in U$, desired exactness ϵ

- 1: **repeat**
 - 2: Calculate full-order state solution $y_{FE} = y(u^\ell)$
 - 3: Calculate POD basis $\psi = \psi(y_{FE})$
 - 4: Apply PDASS on the reduced system (**) to get $u^\ell = u(\psi)$
 - 5: **until** $\text{Aposti}(u^\ell) < \epsilon$
 - 6: Return $\bar{u} = u^\ell$
-



Numerical example

desired state y_Q & state constraint u_b




Fig. 1. The desired state $y_Q \in L^2(0, T; H)$ and the upper mixed control-state bound u_b , interpreted as a pure pointwise state constraint.



Numerical example


optimal state \bar{y} 

Fig. 2. The optimal state solution $\bar{y} \in Y$ satisfying the state constraints.

Universität
Konstanz



Numerical example


optimal control \bar{u} 

Fig. 3. The optimal control term $\mathcal{B}\bar{u} \in L^2(0, T; H)$ controlling the state equation.

Universität
Konstanz



Numerical results





Fig. 4. The ROM errors of the control u^ℓ for different POD basis ranks ℓ , the error bound provided by the a posteriori error estimator and the singular values (squares of the eigenvalues) of the operator $\mathcal{V}\mathcal{V}^*$ which can be used as a costless error indicator.



Numerical effort



Process	Time	#	Total
Assemble full system	0.66 sec	9×	5.97 sec
Solve full system	22.27 sec	9×	200.43 sec
Total			206.40 sec
Solve full snapshots equations	0.11 sec	2×	0.21 sec
Solve eigenvalue problem	0.42 sec	2×	0.84 sec
Assemble ROM system	0.53 sec	17×	9.01 sec
Solve ROM system	0.45 sec	17×	7.72 sec
Evaluate error estimator	0.11 sec	2×	0.23 sec
Total			18.01 sec

Tab. 1. The calculation times for solving the optimization problem with and without model reduction. With 25 POD elements, the ROM problem has to be solved two times; solvings of two eigenvalue problems are required in addition to update the POD basis. Nevertheless, 91.27% of the calculation time is spared in total.

Fig. 5. The numerical effort of the single algorithm processes for solving the ROM problem on an Intel(R) Core(TM) i5 2.40GHz processor.



References

-  Hintermüller, M., Ito, K. & Kunisch, K.: *The primal-dual active set strategy as a semismooth Newton method.*
SIAM J. Optim., **vol. 13**, no. 1: pp. 865–888, 2003.
-  Hintermüller, M., Kopacka, I. & Volkwein, S.: *Mesh-independence and preconditioning for solving parabolic control problems with mixed control-state constraints.*
ESAIM: COVC, **vol. 15**: pp. 626–652, 2009.
-  Hinze, M. & Volkwein, S.: *Error estimates for abstract linear-quadratic optimal control problems using proper orthogonal decomposition.*
Comput. Optim. Appl., **vol. 39**: pp. 319–345, 2008.
-  Tröltzsch, F. & Volkwein, S.: *POD a-posteriori error estimates for linear-quadratic optimal control problems.*
Comput. Optim. Appl., **vol. 44**: pp. 319–345, 2008.
-  Volkwein, S.: *Model Reduction using Proper Orthogonal Decomposition.*
Vorlesungsskript Universität Konstanz, p. 42, 2010.

